

503 Series ELT's

Fully Approved TSO C91a & C-126 COSPAS / SARSAT Approval 97



The need to accurately pin-point downed aircraft through the use of an Emergency Locator Transmitter (ELT) has always existed. The increasing use of both COSPAS/SARSAT and Global Positioning System (GPS) has highlighted the need for an ELT System with expanded range capabilities.

The Techtest 503 ELT System offers just that; full frequency coverage including 121.5MHz, 243MHz and 406.025MHz. The optional inclusion of last known GPS co-ordinates can be input directly into the system or there is the ability to have embedded stand-alone GPS within the G Switch unit.

Housed within high quality durable thermoplastic, the ELT units are through coloured yellow thermoplastic for high visibility.

Unique features of the 503 Series of ELT are the ability to have full remote extended range operation, incorporating a multi-axis G Switch, together with both fixed or portable ELT function in one unit.

Portable operation allows for fast, snap release of the housing, with simple removal of the transmitter unit for use as a man portable Personal Locator beacon should this be required.

FEATURES

- Extended frequency coverage
- Full remote operation
- Fixed and rotary wing operation
- Multi-axis G switch for full aircraft compatibility
- Solid state G switch operation eliminates false/rogue operation
- Fixed/portable options
- Easy aircraft removal for man portable Personal Locator Beacon use
- Modular construction
- GPS option

Headquarters:

Topcast,
 26/F Metropole Square,
 2 On Yiu Street,
 Hong Kong SAR

T: (852) 2305 4111
 F: (852) 2305 4388
 E: inquiries@topcast.com



LinkedIn



www.topcast.com

Specification

Transmitter Signal

Frequency

121.5MHz / 243.0MHz / 406.025 MHz

Peak Effective Radiated Power

0.1W at 121.5 / 243.0MHz

5.0W at 406.025MHz

Frequency Stability

2×10^{-9} per min

Transmission Duration

24Hrs min, 5W PERP at -40°C

48Hrs min, 0.1W PERP at -40°C

Repetition Rate

520ms ($\pm 1\%$) every 50 secs ($\pm 5\%$)

Activation

Manual

The 503 Series of ELT's can be manually operated via the cockpit mounted remote switching panel.

Automatic

The ELT can be reliably activated by the multi-axis G Switch.

Dimensions

255 x 105 x 45mm 1.3kg

Weight

1.3kg

Battery Storage Life

6 years

Approvals

- TSO C91a and C126
- CAA WR01029
- COSPAS/SARSAT Approval No. 97

Compliance

The 503 series of ELT's are compliant with the following specifications:

- COSPAS/SARSAT specification C/ST.001
- EUROCAE ED-62 / RTCA DO-204
- EUROCAE ED-14C / RTCA DO-160C
- CAP 208 Aircraft Radio Equipment Issue 2 January 1991 Volume 1, Part 1

Product Range

Part Number

503-1	Transmitter Only
503-4	Remote Controller
503-7	Multi-axis G Switch Module
503-17	Remote Controller with back lighting
503-19	Multi-axis G Switch Module for helicopter mounting
503-20	Remote Controller with NVG lighting
503-35	Multi-axis G Switch Module with embedded GPS
503-36	Multi-axis G Switch Module with embedded GPS for helicopter mounting

Accessories

Part Number

10-102-19	ELT Rigid Whip Antenna - Aircraft Mounted
10-118-28	ELT Blade Antenna - Aircraft Mounted
10-118-35	ELT/GPS Blade Antenna - Aircraft Mounted
10-274-1	ELT Flexible Whip Antenna - Transmitter Mounted
A0637	Mounting Tray - Portable Installation
A0637-1	Mounting Tray - Fixed Installation
A0638	ELT Fireproof Enclosure



Headquarters:

Topcast,
26/F Metropole Square,
2 On Yiu Street,
Hong Kong SAR

T: (852) 2305 4111
F: (852) 2305 4388
E: inquiries@topcast.com



LinkedIn



www.topcast.com