PERSONAL LOCATOR BEACON 500-30-C SERIES







Bottom View



ACCESSORY CONNECTOR

Remote Activation Switch Ejection seat Parachute Water switch G-Switch


BATTERY

Field replaceable every 5 years (or after activation)

FEATURES

Robust, compact and light-weight Multiple activation methods Increased functionality Speech mode Transmission of 406 MHz and 121.5 MHz and 243MHz SAR frequencies GPS enabled User re-programmable Cospas-Sarsat approved


Top View



SMB ANTENNA CONNECTOR

Trailing Tri-Frequency Antenna for Parachutes or Ejection Seats Life Jacket Antenna

Side View



PERSONAL LOCATOR BEACON 500-30-C SERIES

Exceptional adaptability makes the 500-30 series a perfect fit for military applications, including integration into critical equipment such as life rafts, life vests, flight jackets, and ejection seats. Its unparalleled flexibility offers a tailor-made solution, meticulously crafted to meet the precise needs of the military, all housed within a compact and portable design.

Accessories & Installations



Specification

Weight Dimensions	0.95lbs (430g) 4.98 × 2.76 × 1.30" (126.3 × 70 × 33mm)	Operation	24 hrs (406, 243, 121.5 MHz) Additional 24 hrs (243, 121.5 MHz) -4 to +131°F (operational at -40°F) -20 to +55°C (operational at -40°C)
Colour	NATO Green	Antenna Options	Integral tape antennaTri-Frequency Trailing Tri-Frequency/GPS Antenna for Parachutes or Ejection Seats Life Jacket Tri-Frequency/GPS Antenna
Connectors	1x SMB for additional antennas 1x Mulit-pin for accessories		
C/S Tx	406 MHz (Cospas-Sarsat) including GPS position	Activation Options	ON/OFF/TEST Switch Martin-Baker Auto Activation Cradle Remote Activation Cable Water Switch and/or G-Switch
Homing Tx	121.5 & 243.0 MHz (Homing)		
GPS Rx	72 Channels 2.5m Accuracy		Butler Parachure ARM/OFF Switch Lanyard
Programming	COSPAS-SARSAT message user programmable	Waterproof	33 ft (10 m)
Speech	Push-To-Talk button Two-way on 121.5 & 243.0 MHz	Battery Pack	Field replaceable every 5 years (or after activation)

Compliance

The PLB is compliant with the following specifications:

Civil: EUROCAE ED62A / RTCA DO-204A / EUROCAE ED14F / RTCA DO-160F / COSPAS-SARSAT

Military: NATO - STANAG 7007 / MIL STD 810G





+44(0) 1568 708 744 | sales@hr-smith.com | hr-smith.com

No part of this brochure may be reprinted or duplicated without our consent. All sizes and measurements are approximate but we try to make sure that they are as accurate as possible. In the interest of continuous production development HR Smith reserves the right to alter specification as necessary. E & OE. Issue 01 (Jan '24)